

UPDATED



Gasketed ACCESS DOOR

The Gasketed Access door is an all purpose access door that reduces sound transmission and minimizes air filtration.

FEATURES

EPDM GASKET Reduces sound transmission and minimizes air filtration.

CUSTOM SIZES Custom sizes are available, from 6 inches by 6 inches to 36 inches by 36 inches.

OPTIONAL STAINLESS STEEL The spot-free design on the face of the door gives an aesthetically pleasing appearance

DETAILS

DOOR 16 gauge Steel

FRAME 16 gauge Steel

SIZE

- Min: 6 inches by 6 inches
- Max: 36 inches by 72 inches or 48 inches by 48 inches

INSTALLATION Ceiling or wall

FLANGE 1¼ inch Exposed, Drywall Bead

HINGE Concealed Pin


GASKET EPDM

FINISH White Powder Coat (Steel) or #4 Satin (Stainless Steel)

MATERIALS



White
Powder Coat



#4 Satin
Stainless Steel

FLANGES



1-inch Flange



Drywall Bead


LATCHES



Screwdriver
Cam Latch



Key Operated
Cam Lock



Mortise
Lock Prep



Pinned Hex
Cam Latch



Hex Cam Latch

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X	LENGTH	OPTIONS
BG				X		
	T 1¼ inch Flange W Drywall Bead	C Screwdriver Cam Latch L Key Cam Latch P Pinned Hex Cam Latch M Mortise Prep (1½ inch) Prep H Hex Head Cam	Standard Sizes 6" x 6" 20" x 30" 8" x 8" 22" x 22" 10" x 10" 22" x 30" 12" x 12" 24" x 24" 12" x 18" 24" x 30" 12" x 24" 24" x 36" 14" x 14" 30" x 30" 16" x 16" 30" x 36" 18" x 18" 32" x 32" 18" x 24" 36" x 36"			B Galvannealed S Stainless Steel, Type 304

Rough opening is door size + 1/4 inch minimum.
Additional sizes available, call for more information.

