

BEST-IN-CLASS ACCESS DOOR

for Single Packaged Vertical Heating & Cooling Units

NEW!

- Quick install
- Great Value
- Acoustical Performance
- Great Aesthetics



HVAC Access Door

Distributed by
www.Ameraproducts.com
Phone: (800) 608-6548
Fax: (409) 840-5542
info@ameraproducts.com



HVAC ACCESS DOOR

NEW



HVAC Access Door installation

The HVAC Access Door is available in large sizes to provide easy access for service and repair of equipment.

FEATURES

INSULATED 1½-inch thick fiberglass insulation Linacoustic provides superior acoustical and thermal performance.

RETURN AIR OPTION Perforated return air to meet free air requirements.

EPDM GASKET OPTION Reduces sound transmission and maintains air filtration.

CUSTOM SIZES Custom sizes are available, from 28 inches by 42 inches to 36 inches by 72 inches.

PREHUNG DOOR ALTERNATIVE Requires no additional hardware or trim. Provides a sleek integrated finished look..

DETAILS

DOOR

- 20 gauge Steel
- Liner option 20 gauge Steel

FRAME 16 gauge Steel

SIZE

- Min: 28 inches by 42 inches
- Max: 36 inches by 72 inches

INSTALLATION Wall

FLANGE 1¼ inch Exposed

HINGE Concealed Pin

FINISH White Powder Coat

INSULATION 1½ inch Fiberglass Duct Liner

MATERIALS



White Powder Coat

FLANGES



1¼-inch Flange

LATCHES



Screwdriver Cam Latch



Key Operated Cam Lock



Mortise Lock Prep



Pinned Hex Cam Latch



Hex Cam Latch

ORDER GUIDE

BASE	LATCH	WIDTH	X	LENGTH	OPTIONS
BHVAC			X		
	C Screwdriver Cam Latch	Standard Sizes			G Gasketing Installed
	L Key operated Cam Latch	30" x 48"	34" x 48"		P Perforated Door
	P Pinned Hex Cam Latch	30" x 54"	34" x 54"		N Liner
	M Mortise Prep (1½ inch) Prep	30" x 60"	34" x 60"		
	H Hex Head Cam*	30" x 66"	34" x 66"		
		30" x 72"	34" x 72"		
		32" x 48"	36" x 48"		
		32" x 54"	36" x 54"		
		32" x 60"	36" x 60"		
		32" x 66"	36" x 66"		
		32" x 72"	36" x 72"		

Rough opening is door size + 1/4 inch minimum.
 Additional sizes available, call for more information.
 *Standard Latch.

