Top Security

ACCESS DOOR

Babcock-Davis Top Security Access Door is manufactured with detention-grade materials and provides access through openings in walls. The pan style access door includes a heavy-duty butt hinge welded on the surface of the door to prevent unwanted access.

DETAILS

DOOR 7 Gauge formed steel door

FRAME 3/16 inch Steel Angle - 2 inches by 3 inches

SIZE

Min: 8 inches by 8 inchesMax: 48 inches by 54 inches

INSTALLATION Ceiling or Wall

FLANGE 2" Exposed

HINGE Surface Mounted Heavy-Duty Butt

PAN DEPTH 1-1/4 inch

FINISH White Powder Primer Coat



Distributed by

ww.AmeraProducts.com Phone: (800) 608-6548 Fax: (407) 840-3543 info@ameraproducts.com

ORDER GUIDE

BASE	LATCH	WIDTH	Х	LENGTH	OPTIONS
BTS			Х		
	D Detention Lock Prep M Mortise Lock (1-1/8") Prep	Standard Sizes (W x L) 12" x 12" 22" x 30" 24" x 40"* 16" x 16" 24" x 24" 24" x 48"* 18" x 18" 24" x 36"*		0" 24" x 40"* 1" 24" x 48"*	G Gasketing M Masonry Anchors S Type 304 Stainless Steel

Rough opening is door size + 3/4 inch minimum. Additional sizes available, call for more information. *Recommended for Wall surfaces only.

Draft Stop

ACCESS DOOR

Babcock-Davis Draft Stop Door is a non-rated access door designed to provide access through wall openings in the attics where draft stop conditions are needed. This self-closing and self-latching access door allows for access from both sides of the door.

DETAILS

DOOR 14 gauge Steel (self-closing)

FRAME 16 gauge Steel

SIZE

- Min: 6 inches by 6 inches
- BDT Max: 24 inches by 72 inches, 36 inches by 60 inches or 48 inches by 48 inches
- BDW Max: 36 inches by 48 inches

INSTALLATION Wall

FLANGE Exposed or Drywall Bead

HINGE

- BDT: Flush Continuous Piano
- BDW: Concealed Pin

FINISH White Powder Primer Coat



ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH	X LENGTH	OPTIONS
BD				х	
	T 1 inch Flange W Drywall Bead	K Knurled Knob/ Key Operated 12" Latch Bolt6" x 16" M Mortise Ll®c"x 18" (1-1/8") Prep	24" x 24"	24" x 40"*	B Galvannealed G Gasketing S Type 304 Stainless Steel

Rough opening is door size +1/4 inch minimum.

Additional sizes available, call for more information.

*Recommended for Wall surfaces only.

