Tile Ready FIRE-RATED ACCESS DOOR

The Tile Ready Access Door is UL Listed for openings that may require tile applications. When installed, the door and frame are concealed providing an aesthetically pleasing appearance.

DETAILS

DOOR 14 gauge Steel, Self-Closing

FRAME 16 gauge Steel

SIZE

Min: 8 inches by 8 inchesMax: 24 inches by 24 inches

INSTALLATION Wall

FLANGE Exposed or Drywall Bead

HINGE Cabinet Type

CERTIFICATION UL listed "B" label for 1-1/2 hours

			c UL US
	90	B	

ORDER GUIDE

BASE	FLANGE	LATCH	WIDTH		LENGTH	OPTIONS
BRU				х		
	T 1 inch FlangeW Drywall Bead	K Knurled knob/ key operated latch bolt	Standard Siz 10" × 10" 16 12" × 12" 18	" x 16	" 24" x 24"	S Type 304 Stainless Steel
		M Mortise lock (1-1/8") prep				

Rough opening is door size + 1/4 inch minimum. Additional sizes available, call for more information.

Upward Opening FIRE-RATED ACCESS DOOR

Babcock-Davis' fire-rated Upward Opening Access Door is designed for ceiling applications when the door must swing upward into a ceiling cavity.

• BFRU: 18 gauge Steel

• BFRU: 16 gauge Steel

DETAILS

DOOR

• BIU: 20 gauge Steel

FRAME

• BIU: 16 gauge Steel

SIZE

- BIU Min: 12 inches by 12 inches BFRU Min: 24 inches by 36 inches
- BIU Max: 24 inches by 36 inches BFRU Max: 48 inches by 60 inches

INSTALLATION Ceiling

FLANGE Exposed

HINGE Concealed Continuous Piano

FINISH Off White Prime Coat

INSULATION 2 inch Thick, Fire-Rated Mineral Fiber, R-8

CERTIFICATION Warnock-Hersey listed for 2 hours





Distributed by ww.AmeraProducts.com Phone: (800) 608-6568 rax: (409) 840-5543 info@ameraproducts.com

ORDER GUIDE

BASE	LATCH	WIDTH	Х	LENGTH	OPTIONS
			x		
BIU Sizes <24" x 36"	A Allen Head	Standard	Sizes	B Galvannealed*	
BFRU Sizes >24" x 48"	Key M Mortise Lock (1-1/8") Prep	14" x 14"	22" x 22" x 24" x	 G Gasketing S Type 304 Stainless Steel 	
	ГЕР	BFRU 24" x 48" 30" x 30" 30" x 36"	30") 32") 36")	(32"	

Rough opening is door size + 1/4 inch minimum.

Additional sizes available, call for more information.

Use BIU for access doors 24" x 36" or smaller; BFRU for larger doors. *BIU only



